





TECHNICAL SPECIFICATION

Diameter of wheels	
	700 mm
Maximum Depth under guide	
	325 mm
Maximum Depth of Cut	300 mm
Maximum Distance saw to body	
	680 mm
Maximum Opening to Feed	300 mm
Maximum Opening to multi-roller Fence	230 mm
Saw Motor Power	11 kW (15 hp)
Feed Speed Infinitely Variable	4-25 m/min
Feed Motor Power	0.75 kW (1 hp)
Maximum width of blade	76 mm
	Maximum Depth under guide Maximum Depth of Cut Maximum Distance saw to body Maximum Opening to Feed Maximum Opening to multi-roller Fence Saw Motor Power Feed Speed Infinitely Variable Feed Motor Power





4-25 m/min

0.75 kW (1 hp)

76 mm 5080 mm

4940 mm

1800 m/min

TECHNICAL SPECIFICATION

Feed Speed Infinitely Variable

♦ Feed Motor Power

♦ Maximum width of blade

Maximum length of blade

Minimum length of blade

◆ Speed of blade

Multi Roller Adjustable Fence

◆ Counter Balance Top Guide With Mechanical Adjustment

♦ Bottom Roller Saw Guide

Sawblade Tension Indicator

♦ Cleaning Brushes to Top & Bottom Wheels with Drip Feed

♦ Anti Adherent

♦ 1 x 76.2mm Swage Toothed Bandsaw Blade

◆ Star Delta Starter

Lockable isolator

◆ 110 Volt Control Circuit

• Control Gear with individual no volt release and overload protection

♦ Electrical Interlocking to top and bottom doors

♦ Table tilt restricted to 20 degrees

DC injection braking

The machine conforms to CE safety regulations

STANDARD PRICE EX WORKS

All prices are exclusive of VAT

Prices Quoted are firm for acceptance with 30 days

Delivery: 10 weeks

Payment Terms: 30% deposit with order, 70% prior to dispatch from Leicester

(Pictures are from original brochure)











